



## DIMENSIONS

mm

OVERALL LENGTH	475 - <i>folded stock</i> 681 to 760 - <i>extended stock</i>
OVERALL HEIGHT	233 - <i>without magazine</i> 302 - <i>with magazine</i>
WIDTH	75 - <i>without Picatinny rail</i> 80 - <i>with Picatinny rail</i>

## SIGHTS

Front with protection, adjustable in position  
Rear adjustable in position, elevation and laterality  
Sight radius: 270mm

## SAFETY SELECTOR (ambidextrous)

S: Safe  
1: Semi-auto

## REMARKS

The bolt will stays open after the last shot  
Accessory rail build in upper receiver (Picatinny/MIL-STD-1913)  
2- rail fixing system for standard Picatinny accessories  
Ambidextrous slide catch and magazine release  
3 points carrying sling  
Cleaning kit *(optional)*  
Magazine clip *(optional)*  
Front sight with Tritium *(optional)*

## TECHNICAL DATA



**CALIBER**  
.40S&W



**CAPACITY**  
30



**BARREL LENGTH**  
200mm  
6 right hand  
Twist: 420mm



**ACTION**  
Blowback  
Floating firing pin



**WEIGHT**  
3,350g - without mag.  
3,550g - with mag.



**FINISH**  
Black anodized