



DIMENSIONS

mm

OVERALL LENGTH	475 - <i>folded stock</i> 681 to 760 - <i>extended stock</i>
OVERALL HEIGHT	233 - <i>without magazine</i> 293 - <i>with magazine</i>
WIDTH	75 - <i>without Picatinny rail</i> 80 - <i>with Picatinny rail</i>

SIGHTS

Front with protection, adjustable in position
Rear adjustable in position, elevation and laterality
Sight radius: 270mm

SAFETY SELECTOR (ambidextrous)

S: Safe
1: Semi-auto
2: Limited burst - 2 rounds
F: Full auto (*firing rate: approximately 750 rounds/min*)

REMARKS

The bolt will stays open after the last shot
Accessory rail build in upper receiver (Picatinny/MIL-STD-1913)
2- rail fixing system for standard Picatinny accessories
Ambidextrous slide catch and magazine release
3 points carrying sling
Cleaning kit (*optional*)
Magazine clip (*optional*)
Front sight with Tritium (*optional*)

TECHNICAL DATA



CALIBER
9mm



CAPACITY
30



BARREL LENGTH
200mm
6 right hand
Twist: 250mm



ACTION
Blowback
Floating firing pin



WEIGHT
3,350kg - without mag.
3,550kg - with mag.



FINISH
Black anodized