



## DIMENSIONS

mm

OVERALL LENGTH	716 - <i>retracted buttstock</i> 811 - <i>extended buttstock</i>
OVERALL HEIGHT	223 - <i>without magazine</i> 258 - <i>with magazine</i>
WIDTH	67

## SIGHTS

Front with protection, adjustable in elevation  
Rear adjustable in elevation and direction  
Sight radius: 382mm

## SAFETY SELECTOR

SAFE: Safe  
SEMI: Semi-auto  
AUTO: Full auto (*firing rate: approximately 650-900 rounds/min*)

## REMARKS

The bolt will stays open after the last shot  
Accessory rail build in upper receiver (Picatinny/MIL-STD-1913)  
QUADRIL handguard with 4 Picatinny rails  
Steel magazine  
3 points carrying sling  
Cleaning kit (*optional*)  
STANAG flash hide supresor  
Detachable Carry handle

## TECHNICAL DATA



**CALIBER**  
5,56 NATO



**CAPACITY**  
30



**BARREL LENGTH**  
292,1mm  
6 right hand  
Twist: 1:7



**ACTION**  
Direct impingement  
Gas operated  
Floating firing pin



**WEIGHT**  
3,050kg - without mag.  
3,275kg - with mag.



**FINISH**  
Black matte